



SUB-ASSEMBLY RECORD

MODULE NO. 169  
IDENTITY NO. 169

MODULE DESCRIPTION: PACKER SC2-PAH 9-5/8" 194-60x47

FIELD: PLATFORM: WELL: 169 TYPE:

DESCRIPTION	MODULE DIAGRAM	ACTUAL LENGTH (ft.)	MIN. ID (in.)	MAX. OD (in.)	DRIFT DRIFTED?	ACTUAL TORQUE (ft/lbs)	MATERIAL	PART NO.
<p>BAKER MODEL SC2-PAH RETAINER PRODUCTION PACKER SIZE: 9-5/8" 190-60x47 BOX: VAM AG</p>		5.16	4.750	8.125	YES/NO	13750	AG 13%Cr	646-87-5102 10.30.20.316.9
<p>MILLOUT EXTENSION SIZE: 7" 29 LB/FT BOX: VAM AG PIN: VAM AG</p>		6.00	6.184	7.000	YES/NO	13750	13% Cr	04.30.98.372.9
<p>CROSSOVER SIZE: 7" x 5" BOX: VAM AG PIN: VAM AG</p>		2.00	4.276	7.681	YES/NO	6400	13% Cr	04.88.21.618.9
<p>PUP JOINT VAM AG SIZE: 5" 18 LB/FT BOX: VAM AG PIN: VAM AG</p>		10.0	4.276	5.587	YES/NO	6400	13% Cr	04.30.98.090.9
<p>PUP JOINT SIZE: 5" 18 LB/FT BOX: VAM AG PIN: VAM AG</p>		10.0	4.276	5.563	YES/NO	6400	13% Cr	04.30.98.090.9
<p>BAKER MODEL AF LANDING NIPPLE SIZE: 4" BOX: VAM AG PIN: VAM AG</p>		2.50	4.000	5.750	YES/NO	6400	13% Cr	801-94-6002 10.41.21.026.9
<b>TOTAL ASSEMBLY LENGTH:</b>		.....	<b>TOTAL ASSEMBLY DRIFTED:</b>		YES/NO			

	MIN. TORQUE	OPT. TORQUE	MAX. TORQUE	M.S.P.
7" 29 LB/FT VAM ATAC TUBING	8460	9400	10340	4400
5-1/2" 17 LB/FT VAM ATAC TUBING	4950	5500	6050	2585

DRIFT 3.919 THROUGH ASSEMBLY.  
ENSURE PACKER FITTED WITH 6 BRASS SHEAR SCREWS, SET PLUG TEST TO 5000 PSI ABOVE AND BELOW.  
WORKSHOP TEST PRESSURE : 5000 PSI MAXIMUM.  
USED IN CONJUNCTION WITH 5" LINER COMPLETIONS

NOTE:  
THIS SAMPLE, INCLUDING THE FORM LAYOUT AND EQUIPMENT SYMBOL BLOCKS AND THEIR IMAGES ARE COPYRIGHTED UNDER THE SAME TERMS AND CONDITIONS AS PETROFOCUS COMPLETIONS MANAGER SOFTWARE. PLEASE DO NOT REPRODUCE, COPY OR DISTRIBUTE WITHOUT THE EXPRESS CONSENT OF PETROFOCUS.

I CERTIFY THAT THE ABOVE CHECKS HAVE BEEN CARRIED OUT  
TO: (CO. REP.) \_\_\_\_\_ DATE: \_\_\_\_\_ TO: (CONTRACTOR REP.) \_\_\_\_\_ DATE: \_\_\_\_\_